## **ATTACHMENT 4**

## COMPONENT SCHEDULE (BY ROADWAY)

lina Ita	Item No	S. 6th Street (Willow to Cherry)	I Init	0
ine Item	Item No	Description  Superpave Asphalt Mixture Design, Base Course, PG 64S-22, 3 to < 10 Million ESALs, 25.0mm, 4" Depth,	Unit	Quantity
	4313-0522	Modified	SY	1487
	4350-0106	Subbase 6" Depth (No. 2A), Modified	SY	100
		Superpave Asphalt Mixture Design, Wearing Course, PG 64S-22 3 to <10 million ESALs, 9.5mm Mix, 1 1/2"		
	0413-0298	Depth, SRL-H	SY	9915
		Superpave Asphalt Mixture Design, Wearing Course (Leveling), PG 64S-22 3 to <10 million ESALs, 9.5mm		
	0413-2086	Mix, SRL-H	TN	50
	0413-6055	Superpave Asphalt Mixture Design, Binder Course, PG 64S-22, 3 to < 10 Million ESALs, 19.0mm, 2.5" Depth	SY	1487
	0460-0001	Asphalt Tack Coat	SY	9915
	0491-0012	Milling of Bituminous Pavement Surface, 1.5" Depth, Milled Material Retained by Contractor	SY	9915
	0901-0001	Maintenance and Protection of Traffic During Construction - S. 6th Street	LS	1
	0956-0001	Loop Sensor	LF	250
	0960-0002	4" Yellow Hot Thermoplastic Pavement Markings	LF	2130
	0960-0005	6" White Hot Thermoplastic Pavement Markings	LF	1430
	0960-0021	24" White Hot Thermoplastic Pavement Markings	LF	170
		N. 6th Street (Court to Elm)		
ine Item	Item No	Description	Unit	Quantity
		Superpave Asphalt Mixture Design, Base Course, PG 64S-22, 3 to < 10 Million ESALs, 25.0mm, 4" Depth,		
	4313-0522	Modified	SY	759
	4350-0106	Subbase 6" Depth (No. 2A), Modified	SY	100
		Superpave Asphalt Mixture Design, Wearing Course, PG 64S-22 3 to <10 million ESALs, 9.5mm Mix, 1 1/2"		
	0413-0298	Depth, SRL-H  Superpose Asphalt Mintura Pasign, Magazing Course (Lougling), PC C45, 23,2 to 410 million FCALs, 0 Fmm	SY	5062
	0413-2086	Superpave Asphalt Mixture Design, Wearing Course (Leveling), PG 64S-22 3 to <10 million ESALs, 9.5mm Mix, SRL-H	TN	50
	0413-2080	MIA, SILETI	118	30
	0413-6055	Superpave Asphalt Mixture Design, Binder Course, PG 64S-22, 3 to < 10 Million ESALs, 19.0mm, 2.5" Depth	SY	759
	0460-0001	Asphalt Tack Coat	SY	5062
	0491-0012	Milling of Bituminous Pavement Surface, 1.5" Depth, Milled Material Retained by Contractor	SY	5062
	0901-0002	Maintenance and Protection of Traffic During Construction - N. 6th Street	LS	1
	0960-0005	6" White Hot Thermoplastic Pavement Markings	LF	1852
	0960-0021	24" White Hot Thermoplastic Pavement Markings	LF	102
		S. 8th Street (Franklin to Neversink)		
ne Item	Item No	Description	Unit	Quantity
		Superpave Asphalt Mixture Design, Base Course, PG 64S-22, 3 to < 10 Million ESALs, 25.0mm, 4" Depth,		
	4313-0522	Modified	SY	856
	4350-0106	Subbase 6" Depth (No. 2A), Modified Superpave Asphalt Mixture Design, Wearing Course, PG 64S-22 3 to <10 million ESALs, 9.5mm Mix, 1 1/2"	SY	100
	0413-0298	Depth, SRL-H	SY	5704
	0.120.0230	Superpave Asphalt Mixture Design, Wearing Course (Leveling), PG 64S-22 3 to <10 million ESALs, 9.5mm	5.	3701
	0413-2086	Mix, SRL-H	TN	50
	0413-6055	Superpave Asphalt Mixture Design, Binder Course, PG 64S-22, 3 to < 10 Million ESALs, 19.0mm, 2.5" Depth	SY	856
	0460-0001	Asphalt Tack Coat	SY	5704
	0491-0012	Milling of Bituminous Pavement Surface, 1.5" Depth, Milled Material Retained by Contractor	SY	5704
	0901-0003 0960-0005	Maintenance and Protection of Traffic During Construction - 8th Street 6" White Hot Thermoplastic Pavement Markings	LS LF	1 1486
	0960-0021	24" White Hot Thermoplastic Pavement Markings	LF	102
			-	
		Church Street (Woodward to Court)		
ine Item	Item No	Description	Unit	Quantity
	4242 0525	Superpave Asphalt Mixture Design, Base Course, PG 64S-22, 3 to < 10 Million ESALs, 25.0mm, 4" Depth,	C) '	
	4313-0522	Modified Subbase 6" Depth (No. 2A), Modified	SY	1132
	4350-0106	Superpave Asphalt Mixture Design, Wearing Course, PG 64S-22 3 to <10 million ESALs, 9.5mm Mix, 1 1/2"	SY	150
	0413-0298	Depth, SRL-H	SY	4527
		Superpave Asphalt Mixture Design, Wearing Course (Leveling), PG 64S-22 3 to <10 million ESALs, 9.5mm	- *	,
	0413-2086	Mix, SRL-H	TN	50
	0413-6055	Superpave Asphalt Mixture Design, Binder Course, PG 64S-22, 3 to < 10 Million ESALs, 19.0mm, 2.5" Depth	SY	1132
	0460-0001	Asphalt Tack Coat	SY	4527
	0404 0043	Milling of Dituminary Daysmant Curfors, 1 Fl. Donth, Milled Material Datained by Contractor	C) '	

0491-0012 Milling of Bituminous Pavement Surface, 1.5" Depth, Milled Material Retained by Contractor

Maintenance and Protection of Traffic During Construction - Church Street

0960-0021 24" White Hot Thermoplastic Pavement Markings

0901-0004

4527

1 82

	Item No	Court Street (Bridge to 10th)  Description	Unit	Quant
	4242.0522	Superpave Asphalt Mixture Design, Base Course, PG 64S-22, 3 to < 10 Million ESALs, 25.0mm, 4" Depth,	C) (	00-
	4313-0522	Modified	SY	937
	4350-0106	Subbase 6" Depth (No. 2A), Modified	SY	937
		Superpave Asphalt Mixture Design, Wearing Course, PG 64S-22 3 to <10 million ESALs, 9.5mm Mix, 1 1/2"		
	0413-0298	Depth, SRL-H	SY	4684
		Superpave Asphalt Mixture Design, Wearing Course (Leveling), PG 64S-22 3 to <10 million ESALs, 9.5mm		
	0413-2086	Mix, SRL-H	TN	50
	0442 6055	Conserved Assistant Decision Divides Course DC CAC 23, 24- 440 Million FCAL- 40 Octobr 2 Fill Double	CV.	2776
	0413-6055	Superpave Asphalt Mixture Design, Binder Course, PG 64S-22, 3 to < 10 Million ESALs, 19.0mm, 2.5" Depth	SY	3778
	0460-0001	Asphalt Tack Coat	SY	4684
	0491-0012	Milling of Bituminous Pavement Surface, 1.5" Depth, Milled Material Retained by Contractor	SY	906
	0491-0017	Milling of Bituminous Pavement Surface, 4" Depth, Milled Material Retained by Contractor	SY	3778
	0901-0005	Maintenance and Protection of Traffic During Construction - Court Street	LS	1
	0960-0005	6" White Hot Thermoplastic Pavement Markings	LF	1065
	0960-0021	24" White Hot Thermoplastic Pavement Markings	LF	84
	0960-0102	White Hot Thermoplastic Legend, "STOP", 8'-0"	EACH	2
		Riverfront Drive (S. Front to 2nd)		
Line Item	Item No	Description	Unit	Quant
		Superpave Asphalt Mixture Design, Base Course, PG 64S-22, 3 to < 10 Million ESALs, 25.0mm, 4" Depth,		
	4313-0522	Modified	SY	3212
	4350-0106	Subbase 6" Depth (No. 2A), Modified	SY	150
		Superpave Asphalt Mixture Design, Wearing Course, PG 64S-22 3 to <10 million ESALs, 9.5mm Mix, 1 1/2"		
	0413-0298	Depth, SRL-H	SY	1284
		Superpave Asphalt Mixture Design, Wearing Course (Leveling), PG 64S-22 3 to <10 million ESALs, 9.5mm		
	0413-2086	Mix, SRL-H	TN	100
	0413-6055	Superpave Asphalt Mixture Design, Binder Course, PG 64S-22, 3 to < 10 Million ESALs, 19.0mm, 2.5" Depth	SY	3212
	0460-0001	Asphalt Tack Coat	SY	1284
	0491-0012	Milling of Bituminous Pavement Surface, 1.5" Depth, Milled Material Retained by Contractor	SY	1284
	0901-0006	Maintenance and Protection of Traffic During Construction - Riverfront Drive	LS	1
	0960-0002	4" Yellow Hot Thermoplastic Pavement Markings	LF	5960
	0960-0005	6" White Hot Thermoplastic Pavement Markings	LF	90
	0960-0021	24" White Hot Thermoplastic Pavement Markings	LF	115
	0960-0102	White Hot Thermoplastic Legend, "STOP", 8'-0"	EACH	1
Line Item	Item No	River Road (SR 12 to Muhlenberg Twp Line) Description	Unit	Quant
		Superpave Asphalt Mixture Design, Base Course, PG 64S-22, 3 to < 10 Million ESALs, 25.0mm, 4" Depth,		
	4313-0522	Modified	SY	3208
	4350-0106	Subbase 6" Depth (No. 2A), Modified	SY	250
	4330 0100	Superpave Asphalt Mixture Design, Wearing Course, PG 64S-22 3 to <10 million ESALs, 9.5mm Mix, 1 1/2"	31	230
	0413-0298	Depth, SRL-H	SY	9167
	0413-0238	Superpave Asphalt Mixture Design, Wearing Course (Leveling), PG 64S-22 3 to <10 million ESALs, 9.5mm	31	3107
	0413-2086	Mix, SRL-H	TN	100
	0413-6055	Superpave Asphalt Mixture Design, Binder Course, PG 64S-22, 3 to < 10 Million ESALs, 19.0mm, 2.5" Depth	SY	3208
	0460-0001	Asphalt Tack Coat	SY	9167
	0491-0012	Milling of Bituminous Pavement Surface, 1.5" Depth, Milled Material Retained by Contractor	SY	9167
	0901-0007	Maintenance and Protection of Traffic During Construction - River Road		3107
		Maintenance and Protection of Tranic During Construction - River Road	1.0	1
		All NA/Like 11-4 The superplantia Deviana and Mandriana	LS	1
	0960-0001	4" White Hot Thermoplastic Pavement Markings	LF	7500
		4" White Hot Thermoplastic Pavement Markings 4" Yellow Hot Thermoplastic Pavement Markings		7500
	0960-0001 0960-0002	4" Yellow Hot Thermoplastic Pavement Markings  Riverdale (All Roads)	LF LF	7500 7500
Line Item	0960-0001	4" Yellow Hot Thermoplastic Pavement Markings  Riverdale (All Roads)  Description	LF	7500 7500
Line Item	0960-0001 0960-0002 Item No	4" Yellow Hot Thermoplastic Pavement Markings  Riverdale (All Roads)  Description  Superpave Asphalt Mixture Design, Base Course, PG 64S-22, 3 to < 10 Million ESALs, 25.0mm, 4" Depth,	LF LF <b>Unit</b>	7500 7500 <b>Quant</b>
Line Item	0960-0001 0960-0002 Item No 4313-0522	4" Yellow Hot Thermoplastic Pavement Markings  Riverdale (All Roads)  Description  Superpave Asphalt Mixture Design, Base Course, PG 645-22, 3 to < 10 Million ESALs, 25.0mm, 4" Depth, Modified	LF LF <b>Unit</b>	7500 7500 <b>Quant</b>
Line Item	0960-0001 0960-0002 Item No	4" Yellow Hot Thermoplastic Pavement Markings  Riverdale (All Roads)  Description  Superpave Asphalt Mixture Design, Base Course, PG 64S-22, 3 to < 10 Million ESALs, 25.0mm, 4" Depth, Modified  Subbase 6" Depth (No. 2A), Modified	LF LF <b>Unit</b>	7500 7500 <b>Quant</b>
Line Item	0960-0001 0960-0002 Item No 4313-0522 4350-0106	A" Yellow Hot Thermoplastic Pavement Markings  Riverdale (All Roads)  Description  Superpave Asphalt Mixture Design, Base Course, PG 64S-22, 3 to < 10 Million ESALs, 25.0mm, 4" Depth, Modified Subbase 6" Depth (No. 2A), Modified Superpave Asphalt Mixture Design, Wearing Course, PG 64S-22 3 to <10 million ESALs, 9.5mm Mix, 1 1/2"	LF LF Unit	7500 7500 <b>Quant</b> 7365 500
Line Item	0960-0001 0960-0002 Item No 4313-0522	A" Yellow Hot Thermoplastic Pavement Markings  Riverdale (All Roads)  Description  Superpave Asphalt Mixture Design, Base Course, PG 64S-22, 3 to < 10 Million ESALs, 25.0mm, 4" Depth, Modified Subbase 6" Depth (No. 2A), Modified Superpave Asphalt Mixture Design, Wearing Course, PG 64S-22 3 to <10 million ESALs, 9.5mm Mix, 1 1/2" Depth, SRL-H	LF LF <b>Unit</b>	7500 7500 <b>Quant</b> 7365 500
Line Item	0960-0001 0960-0002 Item No 4313-0522 4350-0106	A" Yellow Hot Thermoplastic Pavement Markings  Riverdale (All Roads)  Description  Superpave Asphalt Mixture Design, Base Course, PG 64S-22, 3 to < 10 Million ESALs, 25.0mm, 4" Depth, Modified Subbase 6" Depth (No. 2A), Modified Superpave Asphalt Mixture Design, Wearing Course, PG 64S-22 3 to <10 million ESALs, 9.5mm Mix, 1 1/2"	LF LF Unit	7500 7500 <b>Quant</b> 7365 500 3682
Line Item	0960-0001 0960-0002 Item No 4313-0522 4350-0106 0413-0298	A" Yellow Hot Thermoplastic Pavement Markings  Riverdale (All Roads)  Description  Superpave Asphalt Mixture Design, Base Course, PG 64S-22, 3 to < 10 Million ESALs, 25.0mm, 4" Depth, Modified  Subbase 6" Depth (No. 2A), Modified  Superpave Asphalt Mixture Design, Wearing Course, PG 64S-22 3 to <10 million ESALs, 9.5mm Mix, 1 1/2" Depth, SRL-H  Superpave Asphalt Mixture Design, Wearing Course (Leveling), PG 64S-22 3 to <10 million ESALs, 9.5mm Mix, 5RL-H	LF LF Unit	7500 7500 <b>Quant</b> 7365 500 3682
Line Item	0960-0001 0960-0002 Item No 4313-0522 4350-0106 0413-0298 0413-2086 0413-6055	Riverdale (All Roads)  Description  Superpave Asphalt Mixture Design, Base Course, PG 64S-22, 3 to < 10 Million ESALs, 25.0mm, 4" Depth, Modified Subbase 6" Depth (No. 2A), Modified Superpave Asphalt Mixture Design, Wearing Course, PG 64S-22 3 to <10 million ESALs, 9.5mm Mix, 1 1/2" Depth, SRL-H Superpave Asphalt Mixture Design, Wearing Course (Leveling), PG 64S-22 3 to <10 million ESALs, 9.5mm Mix, SRL-H Superpave Asphalt Mixture Design, Binder Course, PG 64S-22, 3 to < 10 Million ESALs, 19.0mm, 2.5" Depth	LF LF Unit	7500 7500 <b>Quant</b> 7365 500 3682 250
Line Item	0960-0001 0960-0002 Item No 4313-0522 4350-0106 0413-0298 0413-2086 0413-6055 0460-0001	Riverdale (All Roads)  Description  Superpave Asphalt Mixture Design, Base Course, PG 64S-22, 3 to < 10 Million ESALs, 25.0mm, 4" Depth, Modified Subbase 6" Depth (No. 2A), Modified Superpave Asphalt Mixture Design, Wearing Course, PG 64S-22 3 to <10 million ESALs, 9.5mm Mix, 1 1/2" Depth, SRL-H Superpave Asphalt Mixture Design, Wearing Course (Leveling), PG 64S-22 3 to <10 million ESALs, 9.5mm Mix, 5RL-H Superpave Asphalt Mixture Design, Wearing Course, PG 64S-22 3 to <10 million ESALs, 9.5mm Mix, SRL-H Superpave Asphalt Mixture Design, Binder Course, PG 64S-22, 3 to < 10 Million ESALs, 19.0mm, 2.5" Depth Asphalt Tack Coat	LF LF Unit	7500 7500 <b>Quant</b> 7365 500 3682 250 7365 3682
Line Item	0960-0001 0960-0002 Item No 4313-0522 4350-0106 0413-0298 0413-2086 0413-6055 0460-0001 0491-0012	Riverdale (All Roads)  Description  Superpave Asphalt Mixture Design, Base Course, PG 645-22, 3 to < 10 Million ESALs, 25.0mm, 4" Depth, Modified Subbase 6" Depth (No. 2A), Modified Superpave Asphalt Mixture Design, Wearing Course, PG 64S-22 3 to <10 million ESALs, 9.5mm Mix, 1 1/2" Depth, SRL-H Superpave Asphalt Mixture Design, Wearing Course (Leveling), PG 64S-22 3 to <10 million ESALs, 9.5mm Mix, SRL-H  Superpave Asphalt Mixture Design, Wearing Course (Leveling), PG 64S-22 3 to <10 million ESALs, 9.5mm Mix, SRL-H  Superpave Asphalt Mixture Design, Binder Course, PG 64S-22, 3 to < 10 Million ESALs, 19.0mm, 2.5" Depth Asphalt Tack Coat Milling of Bituminous Pavement Surface, 1.5" Depth, Milled Material Retained by Contractor	LF LF Unit	7500 7500 <b>Quant</b> 7365 500 3682 250 7365 3682 3682
Line Item	0960-0001 0960-0002 Item No 4313-0522 4350-0106 0413-0298 0413-2086 0413-6055 0460-0001	Riverdale (All Roads)  Description  Superpave Asphalt Mixture Design, Base Course, PG 64S-22, 3 to < 10 Million ESALs, 25.0mm, 4" Depth, Modified Subbase 6" Depth (No. 2A), Modified Superpave Asphalt Mixture Design, Wearing Course, PG 64S-22 3 to <10 million ESALs, 9.5mm Mix, 1 1/2" Depth, SRL-H Superpave Asphalt Mixture Design, Wearing Course (Leveling), PG 64S-22 3 to <10 million ESALs, 9.5mm Mix, 5RL-H Superpave Asphalt Mixture Design, Wearing Course, PG 64S-22 3 to <10 million ESALs, 9.5mm Mix, SRL-H Superpave Asphalt Mixture Design, Binder Course, PG 64S-22, 3 to < 10 Million ESALs, 19.0mm, 2.5" Depth Asphalt Tack Coat	LF LF Unit	7500 7500 <b>Quant</b> 7365 500 3682 250 7365 3682
	0960-0001 0960-0002 Item No 4313-0522 4350-0106 0413-0298 0413-2086 0413-6055 0460-0001 0491-0012 0901-0008	Riverdale (All Roads)  Description  Superpave Asphalt Mixture Design, Base Course, PG 64S-22, 3 to < 10 Million ESALs, 25.0mm, 4" Depth, Modified Subbase 6" Depth (No. 2A), Modified Superpave Asphalt Mixture Design, Wearing Course, PG 64S-22 3 to <10 million ESALs, 9.5mm Mix, 11/2" Depth, SRL-H Superpave Asphalt Mixture Design, Wearing Course (Leveling), PG 64S-22 3 to <10 million ESALs, 9.5mm Mix, 5RL-H Superpave Asphalt Mixture Design, Wearing Course (Leveling), PG 64S-22 3 to <10 million ESALs, 9.5mm Mix, SRL-H Superpave Asphalt Mixture Design, Binder Course, PG 64S-22, 3 to < 10 Million ESALs, 19.0mm, 2.5" Depth Asphalt Tack Coat Milling of Bituminous Pavement Surface, 1.5" Depth, Milled Material Retained by Contractor Maintenance and Protection of Traffic During Construction - Riverdale (All Roads)  Pike and Birch Storm Sewer	LF LF Unit	7500 7500 <b>Quant</b> 7365 500 3682 250 7365 3682 3682 1
	0960-0001 0960-0002 Item No 4313-0522 4350-0106 0413-0298 0413-2086 0413-6055 0460-0001 0491-0012	Riverdale (All Roads)  Description  Superpave Asphalt Mixture Design, Base Course, PG 645-22, 3 to < 10 Million ESALs, 25.0mm, 4" Depth, Modified Subbase 6" Depth (No. 2A), Modified Superpave Asphalt Mixture Design, Wearing Course, PG 645-22 3 to <10 million ESALs, 9.5mm Mix, 1 1/2" Depth, SRL-H Superpave Asphalt Mixture Design, Wearing Course (Leveling), PG 64S-22 3 to <10 million ESALs, 9.5mm Mix, 5RL-H Superpave Asphalt Mixture Design, Wearing Course (Leveling), PG 64S-22 3 to <10 million ESALs, 9.5mm Mix, SRL-H Superpave Asphalt Mixture Design, Binder Course, PG 64S-22, 3 to < 10 Million ESALs, 19.0mm, 2.5" Depth Asphalt Tack Coat Milling of Bituminous Pavement Surface, 1.5" Depth, Milled Material Retained by Contractor Maintenance and Protection of Traffic During Construction - Riverdale (All Roads)  Pike and Birch Storm Sewer  Description	LF LF Unit	7500 7500 <b>Quant</b> 7365 500 3682 250 7365 3682 3682 1
	0960-0001 0960-0002 Item No 4313-0522 4350-0106 0413-0298 0413-2086 0413-6055 0460-0001 0491-0012 0901-0008	Riverdale (All Roads)  Description  Superpave Asphalt Mixture Design, Base Course, PG 645-22, 3 to < 10 Million ESALs, 25.0mm, 4" Depth, Modified Subbase 6" Depth (No. 2A), Modified Superpave Asphalt Mixture Design, Wearing Course, PG 64S-22 3 to <10 million ESALs, 9.5mm Mix, 11/2" Depth, SRL-H Superpave Asphalt Mixture Design, Wearing Course (Leveling), PG 64S-22 3 to <10 million ESALs, 9.5mm Mix, 5RL-H  Superpave Asphalt Mixture Design, Binder Course, PG 64S-22, 3 to < 10 Million ESALs, 19.0mm, 2.5" Depth Asphalt Tack Coat Milling of Bituminous Pavement Surface, 1.5" Depth, Milled Material Retained by Contractor Maintenance and Protection of Traffic During Construction - Riverdale (All Roads)  Pike and Birch Storm Sewer  Description  Superpave Asphalt Mixture Design, Base Course, PG 64S-22, 3 to < 10 Million ESALs, 25.0mm, 4" Depth,	LF LF Unit	7500 7500 <b>Quant</b> 7365 500 3682 250 7365 3682 3682 1
Line Item	0960-0001 0960-0002 Item No 4313-0522 4350-0106 0413-0298 0413-2086 0413-6055 0460-0001 0491-0012 0901-0008	Riverdale (All Roads)  Description  Superpave Asphalt Mixture Design, Base Course, PG 645-22, 3 to < 10 Million ESALs, 25.0mm, 4" Depth, Modified Subbase 6" Depth (No. 2A), Modified Superpave Asphalt Mixture Design, Wearing Course, PG 645-22 3 to <10 million ESALs, 9.5mm Mix, 1 1/2" Depth, SRL-H Superpave Asphalt Mixture Design, Wearing Course (Leveling), PG 64S-22 3 to <10 million ESALs, 9.5mm Mix, SRL-H Superpave Asphalt Mixture Design, Wearing Course (Leveling), PG 64S-22 3 to <10 million ESALs, 9.5mm Mix, SRL-H Superpave Asphalt Mixture Design, Binder Course, PG 64S-22, 3 to < 10 Million ESALs, 19.0mm, 2.5" Depth Asphalt Tack Coat Milling of Bituminous Pavement Surface, 1.5" Depth, Milled Material Retained by Contractor Maintenance and Protection of Traffic During Construction - Riverdale (All Roads)  Pike and Birch Storm Sewer  Description  Superpave Asphalt Mixture Design, Base Course, PG 64S-22, 3 to < 10 Million ESALs, 25.0mm, 4" Depth, Modified	LF LF Unit	7500 7500 <b>Quant</b> 7365 500 3682 250 7365 3682 3682 1
	0960-0001 0960-0002 Item No 4313-0522 4350-0106 0413-0298 0413-2086 0413-6055 0460-0001 0491-0012 0901-0008 Item No 4313-0522	Riverdale (All Roads)  Description  Superpave Asphalt Mixture Design, Base Course, PG 64S-22, 3 to < 10 Million ESALs, 25.0mm, 4" Depth, Modified Subbase 6" Depth (No. 2A), Modified Superpave Asphalt Mixture Design, Wearing Course, PG 64S-22 3 to <10 million ESALs, 9.5mm Mix, 1 1/2" Depth, SRL-H Superpave Asphalt Mixture Design, Wearing Course (Leveling), PG 64S-22 3 to <10 million ESALs, 9.5mm Mix, SRL-H Superpave Asphalt Mixture Design, Binder Course, PG 64S-22, 3 to < 10 Million ESALs, 19.0mm, 2.5" Depth Asphalt Tack Coat Milling of Bituminous Pavement Surface, 1.5" Depth, Milled Material Retained by Contractor Maintenance and Protection of Traffic During Construction - Riverdale (All Roads)  Pike and Birch Storm Sewer  Description  Superpave Asphalt Mixture Design, Base Course, PG 64S-22, 3 to < 10 Million ESALs, 25.0mm, 4" Depth, Modified Superpave Asphalt Mixture Design, Wearing Course, PG 64S-22 3 to <10 million ESALs, 9.5mm Mix, 1 1/2"	LF LF Unit	7500 7500 <b>Quant</b> 7369 500 3682 250 7369 3682 3682 1 <b>Quant</b>
	0960-0001 0960-0002 Item No 4313-0522 4350-0106 0413-0298 0413-2086 0413-6055 0460-0001 0491-0012 0901-0008	Riverdale (All Roads)  Description  Superpave Asphalt Mixture Design, Base Course, PG 645-22, 3 to < 10 Million ESALs, 25.0mm, 4" Depth, Modified Subbase 6" Depth (No. 2A), Modified Superpave Asphalt Mixture Design, Wearing Course, PG 645-22 3 to <10 million ESALs, 9.5mm Mix, 1 1/2" Depth, SRL-H Superpave Asphalt Mixture Design, Wearing Course (Leveling), PG 64S-22 3 to <10 million ESALs, 9.5mm Mix, SRL-H Superpave Asphalt Mixture Design, Wearing Course (Leveling), PG 64S-22 3 to <10 million ESALs, 9.5mm Mix, SRL-H Superpave Asphalt Mixture Design, Binder Course, PG 64S-22, 3 to < 10 Million ESALs, 19.0mm, 2.5" Depth Asphalt Tack Coat Milling of Bituminous Pavement Surface, 1.5" Depth, Milled Material Retained by Contractor Maintenance and Protection of Traffic During Construction - Riverdale (All Roads)  Pike and Birch Storm Sewer  Description  Superpave Asphalt Mixture Design, Base Course, PG 64S-22, 3 to < 10 Million ESALs, 25.0mm, 4" Depth, Modified	LF LF Unit	7500 7500 <b>Quant</b> 7365 500 3682 250 7365 3682 3682 1
	0960-0001 0960-0002 Item No 4313-0522 4350-0106 0413-0298 0413-2086 0413-6055 0460-0001 0491-0012 0901-0008 Item No 4313-0522 0413-0298	Riverdale (All Roads)  Description  Superpave Asphalt Mixture Design, Base Course, PG 645-22, 3 to < 10 Million ESALs, 25.0mm, 4" Depth, Modified Subbase 6" Depth (No. 2A), Modified Superpave Asphalt Mixture Design, Wearing Course, PG 645-22 3 to <10 million ESALs, 9.5mm Mix, 1 1/2" Depth, SRL-H Superpave Asphalt Mixture Design, Wearing Course (Leveling), PG 64S-22 3 to <10 million ESALs, 9.5mm Mix, 5RL-H Superpave Asphalt Mixture Design, Binder Course, PG 64S-22, 3 to < 10 Million ESALs, 19.0mm, 2.5" Depth Asphalt Tack Coat Milling of Bituminous Pavement Surface, 1.5" Depth, Milled Material Retained by Contractor Maintenance and Protection of Traffic During Construction - Riverdale (All Roads)  Pike and Birch Storm Sewer  Description  Superpave Asphalt Mixture Design, Base Course, PG 64S-22, 3 to < 10 Million ESALs, 25.0mm, 4" Depth, Modified Superpave Asphalt Mixture Design, Wearing Course, PG 64S-22 3 to <10 million ESALs, 9.5mm Mix, 1 1/2" Depth, SRL-H	LF LF Unit	7500 7500 7500 Quant 7365 500 3682 250 7365 3682 3682 1 Quant 6
	0960-0001 0960-0002 Item No 4313-0522 4350-0106 0413-0298 0413-2086 0413-6055 0460-0001 0491-0012 0901-0008 Item No 4313-0522 0413-0298 0413-6055	Riverdale (All Roads)  Description  Superpave Asphalt Mixture Design, Base Course, PG 64S-22, 3 to < 10 Million ESALs, 25.0mm, 4" Depth, Modified Subbase 6" Depth (No. 2A), Modified Superpave Asphalt Mixture Design, Wearing Course, PG 64S-22 3 to <10 million ESALs, 9.5mm Mix, 1 1/2" Depth, SRL-H Superpave Asphalt Mixture Design, Wearing Course (Leveling), PG 64S-22 3 to <10 million ESALs, 9.5mm Mix, 5RL-H  Superpave Asphalt Mixture Design, Binder Course, PG 64S-22, 3 to < 10 Million ESALs, 19.0mm, 2.5" Depth Asphalt Tack Coat Milling of Bituminous Pavement Surface, 1.5" Depth, Milled Material Retained by Contractor Maintenance and Protection of Traffic During Construction - Riverdale (All Roads)  Pike and Birch Storm Sewer  Description  Superpave Asphalt Mixture Design, Base Course, PG 64S-22, 3 to < 10 Million ESALs, 25.0mm, 4" Depth, Modified Superpave Asphalt Mixture Design, Wearing Course, PG 64S-22 3 to <10 million ESALs, 9.5mm Mix, 1 1/2" Depth, SRL-H  Superpave Asphalt Mixture Design, Binder Course, PG 64S-22, 3 to < 10 Million ESALs, 19.0mm, 2.5" Depth	LF LF LF Unit SY SY TN SY SY LS Unit	7500 7500 7500 Quant 7365 500 3682 250 7365 3682 3682 1 Quant 6
	0960-0001 0960-0002 Item No 4313-0522 4350-0106 0413-0298 0413-2086 0413-6055 0460-0001 0491-0012 0901-0008 Item No 4313-0522 0413-0298 0413-6055 0601-8305	Riverdale (All Roads)  Description  Superpave Asphalt Mixture Design, Base Course, PG 645-22, 3 to < 10 Million ESALs, 25.0mm, 4" Depth, Modified Subbase 6" Depth (No. 2A), Modified Superpave Asphalt Mixture Design, Wearing Course, PG 645-22 3 to <10 million ESALs, 9.5mm Mix, 1 1/2" Depth, SRL-H Superpave Asphalt Mixture Design, Wearing Course (Leveling), PG 64S-22 3 to <10 million ESALs, 9.5mm Mix, 1 1/2" Depth, SRL-H Superpave Asphalt Mixture Design, Binder Course, PG 64S-22, 3 to < 10 Million ESALs, 19.0mm, 2.5" Depth Asphalt Tack Coat Milling of Bituminous Pavement Surface, 1.5" Depth, Milled Material Retained by Contractor Maintenance and Protection of Traffic During Construction - Riverdale (All Roads)  Pike and Birch Storm Sewer  Description  Superpave Asphalt Mixture Design, Base Course, PG 64S-22, 3 to < 10 Million ESALs, 25.0mm, 4" Depth, Modified Superpave Asphalt Mixture Design, Wearing Course, PG 64S-22 3 to < 10 million ESALs, 9.5mm Mix, 1 1/2" Depth, SRL-H  Superpave Asphalt Mixture Design, Binder Course, PG 64S-22, 3 to < 10 Million ESALs, 19.0mm, 2.5" Depth 12" Reinforced Concrete Pipe, Type B < 1.5' Fill	LF LF LF  Unit  SY SY TN SY SY LS  Unit  SY SY LS	7500 7500  Quant 7363 500 3682 250 7363 3682 1  Quant 6 9 6 16
	0960-0001 0960-0002 Item No 4313-0522 4350-0106 0413-0298 0413-2086 0413-6055 0460-0001 0491-0012 0901-0008 Item No 4313-0522 0413-0298 0413-6055 0601-8305 0605-2711	Riverdale (All Roads)  Description  Superpave Asphalt Mixture Design, Base Course, PG 64S-22, 3 to < 10 Million ESALs, 25.0mm, 4" Depth, Modified Subbase 6" Depth (No. 2A), Modified Superpave Asphalt Mixture Design, Wearing Course, PG 64S-22 3 to <10 million ESALs, 9.5mm Mix, 1 1/2" Depth, SRL-H Superpave Asphalt Mixture Design, Wearing Course (Leveling), PG 64S-22 3 to <10 million ESALs, 9.5mm Mix, SRH Superpave Asphalt Mixture Design, Binder Course, PG 64S-22, 3 to < 10 Million ESALs, 19.0mm, 2.5" Depth Asphalt Tack Coat Milling of Bituminous Pavement Surface, 1.5" Depth, Milled Material Retained by Contractor Maintenance and Protection of Traffic During Construction - Riverdale (All Roads)  Pike and Birch Storm Sewer  Description  Superpave Asphalt Mixture Design, Base Course, PG 64S-22, 3 to < 10 Million ESALs, 25.0mm, 4" Depth, Modified Superpave Asphalt Mixture Design, Wearing Course, PG 64S-22 3 to < 10 million ESALs, 9.5mm Mix, 1 1/2" Depth, SRL-H  Superpave Asphalt Mixture Design, Binder Course, PG 64S-22, 3 to < 10 Million ESALs, 19.0mm, 2.5" Depth 12" Reinforced Concrete Pipe, Type B < 1.5' Fill Type C Concrete Top Unit and Bicycle Safe Grate	LF LF Unit  SY SY TN SY SY SY LS Unit  SY SY LS	7500 7500  Quant 7365 500 3682 250 7365 3682 3682 1  Quant 6 9 6 16 1
	0960-0001 0960-0002 Item No 4313-0522 4350-0106 0413-0298 0413-2086 0413-6055 0460-0001 0491-0012 0901-0008 Item No 4313-0522 0413-0298 0413-6055 0601-8305	Riverdale (All Roads)  Description  Superpave Asphalt Mixture Design, Base Course, PG 645-22, 3 to < 10 Million ESALs, 25.0mm, 4" Depth, Modified Subbase 6" Depth (No. 2A), Modified Superpave Asphalt Mixture Design, Wearing Course, PG 645-22 3 to <10 million ESALs, 9.5mm Mix, 1 1/2" Depth, SRL-H Superpave Asphalt Mixture Design, Wearing Course (Leveling), PG 64S-22 3 to <10 million ESALs, 9.5mm Mix, 1 1/2" Depth, SRL-H Superpave Asphalt Mixture Design, Binder Course, PG 64S-22, 3 to < 10 Million ESALs, 19.0mm, 2.5" Depth Asphalt Tack Coat Milling of Bituminous Pavement Surface, 1.5" Depth, Milled Material Retained by Contractor Maintenance and Protection of Traffic During Construction - Riverdale (All Roads)  Pike and Birch Storm Sewer  Description  Superpave Asphalt Mixture Design, Base Course, PG 64S-22, 3 to < 10 Million ESALs, 25.0mm, 4" Depth, Modified Superpave Asphalt Mixture Design, Wearing Course, PG 64S-22 3 to < 10 million ESALs, 9.5mm Mix, 1 1/2" Depth, SRL-H  Superpave Asphalt Mixture Design, Binder Course, PG 64S-22, 3 to < 10 Million ESALs, 19.0mm, 2.5" Depth 12" Reinforced Concrete Pipe, Type B < 1.5' Fill	LF LF LF  Unit  SY SY TN SY SY LS  Unit  SY SY LS	7500 7500  Quant 7363 500 3682 250 7363 3682 1  Quant 6 9 6 16